

Essential Requirements (ER)

For

2-Wire Telephone equipment

(With Nine variants)

Index:

S.N.	Title	Page No.
1.	Scope	
	1.1 Variants	
	1.2 Brief Description	
2.	Essential Requirements	
	2.1 EMI/EMC Requirements	
	2.2 Safety Requirements	
	2.3 Security Requirements (if any)	
	2.4 Technical Requirements	
	2.5 Other Requirements	
	Table-I - Products variants	
	Table-II - List of Interfaces for products and their variants	
	Table-III A - List of Interface parameters and their international standards	
	Table-III B - List of additional test parameters applicable to products	

1. Scope:

This document lays down the Essential Requirements (ER) under the Mandatory Testing Framework in accordance with Government of India Gazette Notification No. G.S.R. 1131 (E), dated 5th September 2017, for “2-Wire Telephone equipment” used in Indian Telecom Networks.

1.1 Variants:

This document covers the following nine variants of the product “2-Wire Telephone equipment” (Please refer Table-I Below):-

Table I: Product and product variants									
Variants→ Products↓	Variant 1	Variant 2	Variant 3	Variant 4	Variant 5	Variant 6	Variant 7	Variant 8	Variant 9
2-Wire Telephone equipment	Executive Telephone System	NSD/ISD Payphone	Electronic Telephone Instrument	Key Telephone Systems	2-Line Feature Phone	Coin Box Telephone	Coin Box Telephone (Table Top interface)	Terminals for connecting to PSTN	CLIP Phone

1.2 Brief Description

This Document covers the following aspects of the Essential Requirements, namely-EMI/EMC Requirements, Safety Requirements, Security Requirements, Technical Requirements and Other Requirements (if any).

2. Essential Requirements

Essential Requirements, namely-EMI/EMC Requirements, Safety Requirements, Security Requirements, Technical Requirements and Other Requirements (if any) are as follows:

2.1 EMI/EMC Requirement:

The equipment shall conform to the EMC requirements as per the following standards and limits indicated therein.

S.N.	Parameter	Results
i)	<p>Conducted and radiated emission:</p> <p>Name of EMC Standard: "CISPR 22 (2008)/CISPR 32- Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment".</p> <p>Limits:-</p> <ul style="list-style-type: none">i. To comply with Class B of CISPR 22 (2008)/CISPR 32.ii. The values of limits shall be as per TEC Standard No. TEC/SD/DD/EMC-221/05.OCT 2016.iii. For Radiated Emission tests, limits below 1 GHz shall be as per Table 4 (a1) or 5 (a1) of TEC Standard No. TEC/SD/DD/EMC-221/05.OCT 2016 for measuring distance of 3m.	Test results from Designated CAB of TEC to be submitted for compliance.
ii)	<p>Immunity to Electrostatic discharge:</p> <p>Name of EMC Standard: IEC 61000-4-2 {2008} "Testing and measurement techniques of Electrostatic discharge immunity test".</p> <p>Limits: -</p> <ul style="list-style-type: none">i. Contact discharge level 2 {± 4 kV} or higher voltage;ii. Air discharge level 3 {± 8 kV} or higher voltage;	Test results from Designated CAB of TEC to be submitted for compliance

iii)	<p>Immunity to radiated RF:</p> <p>Name of EMC Standard: IEC 61000-4-3 (2010) "Testing and measurement techniques- Radiated RF Electromagnetic Field Immunity test"</p> <p>Limits:-</p> <p>For Telecom Equipment and Telecom Terminal Equipment with Voice interface (s)</p> <ul style="list-style-type: none"> i. Under Test level 2 {Test field strength of 3 V/m} for general purposes in frequency range 80 MHz to 1000 MHz and ii. Under test level 3 (10 V/m) for protection against digital radio telephones and other RF devices in frequency ranges 800 MHz to 960 MHz and 1.4 GHz to 6.0 GHz. 	<p>Test results from Designated CAB of TEC to be submitted for compliance</p>
iv)	<p>Immunity to fast transients (burst):</p> <p>Name of EMC Standard: IEC 61000- 4- 4 {2012} "Testing and measurement techniques of electrical fast transients/burst immunity test"</p> <p>Limits:-</p> <p>Test Level 2 i.e. a) 1 kV for AC/DC power lines; b) 0. 5 kV for signal / control / data / telecom lines;</p>	<p>Test results from Designated CAB of TEC to be submitted for compliance</p>
v)	<p>Immunity to surges:</p> <p>Name of EMC Standard: IEC 61000-4-5 (2014) "Testing & Measurement techniques for Surge immunity test"</p> <p>Limits:-</p> <ul style="list-style-type: none"> i. For mains power input ports: <ul style="list-style-type: none"> (a) 2 kV peak open circuit voltage for line to ground coupling (b) 1 kV peak open circuit voltage for line to line coupling ii. For telecom ports: 	<p>Test results from Designated CAB of TEC to be submitted for compliance</p>

	(a) 2 kV peak open circuit voltage for line to ground (b) 2 kV peak open circuit voltage for line to line coupling.	
vi)	<p>Immunity to conducted disturbance induced by Radio frequency fields:</p> <p>Name of EMC Standard: IEC 61000-4-6 (2013) "Testing & measurement techniques- Immunity to conducted disturbances induced by radio- frequency fields"</p> <p>Limits:- Under the test level 2 {3 V r.m.s.}in the frequency range 150 kHz-80 MHz for AC / DC lines and Signal /Control/telecom lines.</p>	Test results from Designated CAB of TEC to be submitted for compliance
vii)	<p>Immunity to voltage dips & short interruptions (applicable to only ac mains power input ports, if any):</p> <p>Name of EMC Standard: IEC 61000-4-11 (2004) "Testing & measurement techniques- voltage dips, short interruptions and voltage variations immunity tests"</p> <p>Limits:-</p> <ul style="list-style-type: none"> i. a voltage dip corresponding to a reduction of the supply voltage of 30% for 500ms (i.e. 70 % supply voltage for 500ms) ii. a voltage dip corresponding to a reduction of the supply voltage of 60% for 200ms; (i.e. 40% supply voltage for 200ms) iii. a voltage interruption corresponding to a reduction of supply voltage of > 95% for 5s. iv. a voltage interruption corresponding to a reduction of supply voltage of >95% for 10ms. 	Test results from Designated CAB of TEC to be submitted for compliance

Note: For checking compliance with the above EMC requirements, the method of measurements shall be in accordance with TEC Standard No. TEC/SD/RD/EMC-002/02.OCT.2016 and the references mentioned therein.

2.2 Safety Requirements:

S.N.	Parameter	Limits	Results
i)	The device shall conform to IS 13252 (2003) (Clause NO. 2.3, 2.9, 5.1, 5.2, 6.1, 6.2, 6.3 and 7.2) "Safety of information technology device including electrical business device" {equivalent to IEC Publication 60950 (2001)}.	Compliance	

2.3 Security Requirements:

As and when prescribed by DoT.

2.4 Technical Requirements:

For technical requirements, refer Table-II for interfaces used for product variants, Table-III A for Interface parameters and Table III B for other test parameters for product variants.

Table II: List of Interfaces for products and their variants									
Applicable to→ Interface ↓	Product Variants								
	Executive Telephone System	NSD/ISD Payphone	Electronic Telephone Instrument	Key Telephone Systems	2-Line Feature Phone	Coin Box Telephone	Coin Box Telephone (Table Top interface)	Terminals for connecting to PSTN	CLIP Phone
2 Wire/PSTN	y	y	y	y	y	y	y	y	y
ISDN/BRI				y					

Table III-A: List of Interface parameters and their international standards			
Applicable to→ Test Parameter ↓	(Standards)	2-Wire/ PSTN	ISDN/BRI
Longitudinal/ Transverse Conversion Loss/ (Impedance Unbalance about earth)	Q.552 (clause 2.1.2)	y	
Return Loss	Q.552(clause 2.1.1.2)	y	
Over Voltage/ Over Current Protection	K.21	y	
Max. Loop Current	ETSI EN 300 01(<60 mA)	y	
Idle State Current	ETSI EN 300 001 (< 30 μA)	y	
Insulation Test	ETSI EN 300 001(>5 MΩ)	y	
Layer III specification	Q.931 (Refer Annexure-I)		y

Table III-B: List of additional test parameters applicable to products										
Applicable to→ Test Parameter ↓	(Standards)	Product Variants								
		Executive Telephone System	NSD/ISD Payphone	Electronic Telephone Instrument	Key Telephone Systems	2-Line Feature Phone	Coin Box Telephone	Coin Box Telephone (Table Top interface)	Terminals for connecting to PSTN	CLIP Phone
Acoustic Shock Absorption	P.360	y	y	y	y	y	y	y	y	y

2.5 Other Requirements (if any): NIL

Annexure-I

Layer –III Specification as per Q.931 for ISDN BRI-S, BRI-U and PRI:

Test Parameter	Standard
Messages for circuit-mode connection basic call control.	
ALERTING	Q.931 (Clause no. 3.1.1)
CALL PROCEEDING	Q.931 (Clause no. 3.1.2)
CONNECT	Q.931 (Clause no. 3.1.3)
SETUP	Q.931 (Clause no. 3.1.14)
SETUP ACKNOWLEDGE	Q.931 (Clause no. 3.1.15)
DISCONNECT	Q.931 (Clause no. 3.1.5)
RELEASE	Q.931 (Clause no. 3.1.9)
RELEASE COMPLETE	Q.931 (Clause no. 3.1.10)
Bearer capability	Q.931 (Clause no. 4.5.5)
Called party number	Q.931 (Clause no. 4.5.8)
Calling party number	Q.931 (Clause no. 4.5.10)
Channel identification	Q.931 (Clause no. 4.5.13)
Call clearing	
Normal call clearing	Q.931 (As per Table 6-5)
User Busy	Q.931 (As per Table 6-5)
Invalid number format or incomplete number	Q.931 (As per Table 6-5)
No answer	Q.931 (As per Table 6-5)