

ER for Smart Security Camera

Scope

This document lays down the Essential Requirements under the mandatory testing Framework in accordance with Government of India Gazette Notification No. G.S.R. 1131(E), dated 05th September 2017, for Smart Security Camera to be used in Indian Telecom Network using cellular technology (2G/3G/4G etc.) or fixed line broadband.

Product Matrix: -

| Product/ Variant | BLE | RFID | NFC | Wi-Fi | GSM 2G | CDMA 2000 | WCDMA 3G | LTE/ LTE-A | USB | SAR | IPv6 | Fixed Line BB |
|--------------------------|-----|------|-----|-------|-----------|--------------|-------------|---------------|-----|-----|------|------------------|
| Smart Security Camera | | NA | | | | | | | | NA | | |

1 EMI/ EMC Requirements

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|------------|--|--|--------------------------|---|
| 1.0 | EMI/ EMC | | | |
| 1.1 | <p>Conducted and Radiated Emission (Class A or B)?</p> <p>The values of limits shall be as per TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> <p>For Radiated Emission tests, limits below 1 GHz shall be as per Table 4 (a1) (for Class B) or 5 (a1) (for Class A) for measuring distance of 3m</p> | CISPR 22 (2008)/ CISPR 32 (2015) Class A or B | Compliance | <i>As CISPR 32: 2015 has replaced CISPR 22: 2008 and the overlap period of 3 years between the two standards as provided by IEC is over in 2018</i> |
| 1.2 | <p>Immunity to Electrostatic discharge: Contact discharge level 2 {± 4 kV} or higher voltage;</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | IEC-61000-4-2 | Compliance | |
| 1.3 | <p>Immunity to Electrostatic discharge: Air discharge level 3 {± 8 kV} or higher voltage.</p> <p>Performance Criteria shall be as per Table 1 under</p> | IEC-61000-4-2 | Compliance | |

| | | | | |
|-----|--|----------------------|------------|--|
| | <p>Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | | | |
| 1.4 | <p>Immunity to radiated RF: Under Test level 2 {Test field strength of 3 V/m} for general purposes in frequency range 80 MHz to 1000 MHz and for protection against digital radio telephones and other RF devices in frequency ranges 800 MHz to 960 MHz and 1.4 GHz to 6.0 GHz.</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | IEC 61000-4-3 (2010) | Compliance | |
| 1.5 | <p>Immunity to fast transients (burst): Test Level 2: 0.5 kV for signal / control / data / telecom lines.</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | IEC 61000-4-4 (2012) | Compliance | |

| | | | | |
|-----|---|---|------------|--|
| 1.6 | <p>Immunity to surges: (a) 2 kV peak open circuit voltage for line to ground</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | <p>IEC 61000-4-5 (2014)</p> <p>Note: For non-rechargeable fixed battery operated device without any telecom or power port, this test is not applicable</p> | Compliance | |
| 1.7 | <p>Immunity to surges: (b) 2 kV peak open circuit voltage for line to line coupling.</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | <p>IEC 61000-4-5 (2014)</p> <p>Note: For non-rechargeable fixed battery operated device without any telecom or power port, this test is not applicable</p> | Compliance | |
| 1.8 | <p>Immunity to conducted disturbance induced by Radio frequency fields: Under the test level 2 {3 V r.m.s.} in the frequency range 150 kHz-80 MHz</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No.</p> | <p>IEC 61000-4-6 (2013)</p> | Compliance | |

| | | | | |
|-----|---|--|------------|--|
| | TEC/SD/DD/EMC-221/05/OCT-16 | | | |
| 1.9 | <p>Immunity to voltage dips & short interruptions (applicable to only ac mains power input ports, if any)</p> <p>Performance Criteria shall be as per Table 1 under Clause 6 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16.</p> <p>Applicable Performance Criteria shall be as per Table 3 under Clause 7.2 of TEC Standard No. TEC/SD/DD/EMC-221/05/OCT-16</p> | <p>IEC 61000-4-11 (2004)</p> <p>IEC 61000-4-29 applicable for product operated in DC below 16A</p> | Compliance | |

2 Safety Requirements

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|---------------|----------------------------|-------------------------|---------------------------------|----------------|
| 2.1 | General Safety Requirement | IS 13252-1/ IEC 60950-1 | Compliance | |

3 Security Requirements

As and when prescribed by DoT

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|---------------|------------------|-----------------|---------------------------------|----------------|
| 3.0 | | | | |

4 Technical Requirements

4.1 Technical Requirements for GSM

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|--------|---|--|--------------------------|---------|
| 4.1.1. | <p>Operating Frequency</p> <p>EUT shall be capable of at least operating in the following frequency bands. GSM: 1710-1785 MHz (U/L) and 1805-1880 MHz (D/L) GSM: 890-915 MHz (U/L) and 935-960 MHz (D/L)</p> | Current National Frequency Allocation Plan | Compliance | |
| 4.1.2. | Transmitter Maximum output power | 3GPP TS 51 010-1 13.16.2 (GPRS) and 3GPP TS 51 010-1 13.3 (GSM) or EN 301 511 (GSM) 4.2.10 | Compliance | |
| 4.1.3. | Output RF Spectrum | 3GPP TS 51 010-1 13.4 or EN 301 511 (GSM) 4.2.6 | Compliance | |
| 4.1.4. | Transmitter spurious emissions in active mode (Conducted) | 3GPP TS 51 010-1 12.1.1 or EN 301 511 (GSM) 4.2.12 | Compliance | |
| 4.1.5. | Receiver spurious emission in idle mode (Conducted) | 3GPP TS 51 010-1 12.1.2 or EN 301 511 (GSM) 4.2.13 | Compliance | |

| | | | | |
|--------|--------------------------------------|---|------------|--|
| 4.1.6. | Frequency Stability | 3GPP TS 51 010-1 13.1 or EN 301 511 (GSM) 4.2.1 | Compliance | |
| 4.1.7. | Receiver Reference sensitivity level | 3GPP TS 51 010-1 14.2.1 or EN 301 511 (GSM) | Compliance | |
| 4.1.8. | Adjacent Channel Rejection | 3GPP TS 51 010-1 14.5.1 or EN 301 511 (GSM) | Compliance | |
| 4.1.9. | Receiver blocking | 3GPP TS 51 010-1 14.7.1 or EN 301 511 (GSM) 4.2.20 | Compliance | |

4.2 Technical Requirements for WCDMA/HSPA

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|--------|---|--|--------------------------|---------|
| 4.2.1. | <p>Operating Frequency</p> <p>EUT shall be capable of at least operating in the following frequency bands. WCDMA: 1920-1980 MHz (U/L) and 2110-2170 MHz (D/L) WCDMA: 890-915 MHz (U/L) and 935-960 MHz (D/L)</p> | Current National Frequency Allocation Plan | Compliance | |
| 4.2.2. | Transmitter Maximum output power | 3GPP TS 34.121-1 5.2 or EN 301 908-2 (UMTS) 4.2.2 | Compliance | |
| 4.2.3. | Transmitter Spectrum emissions mask | 3GPP TS 34.121-1 5.9 or EN 301 908-2 (UMTS) 4.2.3 | Compliance | |
| 4.2.4. | Transmitter spurious emissions in active mode (Conducted) | 3GPP TS 34.121-1 5.11 or EN 301 908-2 (UMTS) 4.2.4 | Compliance | |
| 4.2.5. | Receiver spurious emission in idle mode (Conducted) | 3GPP TS 34.121-1 6.8 or EN 301 908-2 (UMTS) 4.2.10 | Compliance | |
| 4.2.6. | Frequency Stability | 3GPP TS 34.121-1 5.3 or EN 301 908-2 (UMTS) | Compliance | |

| | | | | |
|---------|---|--|------------|--|
| | | | | |
| 4.2.7. | Transmitter Minimum Output Power | 3GPP TS 34.121-1 5.4.3 or EN 301 908-2 (UMTS) 4.2.5 | Compliance | |
| 4.2.8. | Receiver Reference sensitivity level | 3GPP TS 34.121-1 6.2 or EN 301 908-2 (UMTS) 4.2.13 | Compliance | |
| 4.2.9. | Receiver Adjacent Channel Selectivity (ACS) | 3GPP TS 34.121-1 6.4 or EN 301 908-2 (UMTS) 4.2.6 | Compliance | |
| 4.2.10. | Receiver In-band blocking | 3GPP TS 34.121-1 6.5.2.1 or EN 301 908-2 (UMTS) 4.2.7 | Compliance | |

4.3 Technical Requirements for LTE/LTE-A

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|--------|--|--|--------------------------|---------|
| 4.3.1. | <p>Operating Frequency</p> <p>EUT shall be capable of operating in FDD bands or TDD bands or both FDD and TDD bands as mentioned below as per the band allocation to different operators.</p> <p>LTE(FDD):824 – 849 MHz (U/L) and 869 – 894 MHz (D/L)</p> <p>LTE(FDD):1710-1785 MHz (U/L) and 1805-1880 MHz (D/L)</p> <p>LTE(FDD): 1920-1980 MHz (U/L) and 2110-2170 MHz (D/L)</p> <p>LTE (TDD): 2300 – 2400 MHz</p> <p>LTE (TDD): 2496 – 2690 MHz</p> | Current National Frequency Allocation Plan | Compliance | |

| | | | | |
|---------|---|---|------------|--|
| 4.3.2. | Transmitter Maximum output power | 3GPP TS 36.521-1 6.2.2 or EN 301 908-13 (LTE) 4.2.2 | Compliance | |
| 4.3.3. | Transmitter Spectrum emissions mask | 3GPP TS 36.521-1 6.6.2.1 or EN 301 908-13 (LTE) 4.2.3 | Compliance | |
| 4.3.4. | Transmitter spurious emissions in active mode (Conducted) | 3GPP TS 36.521-1 6.6.3.1, 6.6.3.2, 6.6.3.3 or EN 301 908-13 (LTE) 4.2.4 | Compliance | |
| 4.3.5. | Receiver spurious emission in idle mode (Conducted) | 3GPP TS 36.521-1 7.9 or EN 301 908-13 (LTE) 4.2.10 | Compliance | |
| 4.3.6. | Frequency Stability | 3GPP TS 36.521-1 6.5 or EN 301 908-13 (LTE) | Compliance | |
| 4.3.7. | Power Control Absolute power tolerance | 3GPP TS 36.521-1 6.3.5.1 or EN 301 908-13 (LTE) | Compliance | |
| 4.3.8. | Receiver Reference sensitivity level | 3GPP TS 36.521-1 7.3 or EN 301 908-13 (LTE) 4.2.12 | Compliance | |
| 4.3.9. | Receiver Adjacent Channel Selectivity (ACS) | 3GPP TS 36.521-1 7.5 or EN 301 908-13 (LTE) 4.2.6 | Compliance | |
| 4.3.10. | Receiver In-band blocking | 3GPP TS 36.521-1 7.6.1 or EN 301 908-13 (LTE) 4.2.7 | Compliance | |

4.4 Technical Requirements for CDMA 2000

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|--------|--|--|--------------------------|---------|
| 4.4.1. | Operating Frequency EUT shall be capable of at least operating in the following frequency bands. CDMA: 824-844 MHz (U/L) and 869-889 MHz (D/L) | Current National Frequency Allocation Plan | Compliance | |
| 4.4.2. | Transmitter Maximum output power | 1x: S0011 4.4.5 or EN 301 908-04 (CDMA) 4.2.3 | Compliance | |
| 4.4.3. | Transmitter Spectrum emissions mask | 1x: S0011 4.5.1 or EN 301 908-04 (CDMA) 4.2.2 | Compliance | |
| 4.4.4. | Transmitter spurious emissions in active mode (Conducted) | 1x: S0011 4.5.1 or EN 301 908-04 (CDMA) 4.2.2 | Compliance | |
| 4.4.5. | Receiver spurious emission in idle mode (Conducted) | 1x: S0011 3.6 or EN 301 908-04 (CDMA) 4.2.5 | Compliance | |
| 4.4.6. | Frequency Stability | 1x: S0011 4.1 or EN 301 908-04 (CDMA) | Compliance | |
| 4.4.7. | Receiver Reference sensitivity level | EN 301 908-04 (CDMA) | Compliance | |
| 4.4.8. | Receiver Adjacent | EN 301 908-04 (CDMA) 4.2.8 | Compliance | |

| | | | | |
|--------|------------------------------|----------------------------|------------|--|
| | Channel Selectivity (ACS) | | | |
| 4.4.9. | Receiver In-band blocking | EN 301 908-04 (CDMA) 4.2.6 | Compliance | |

4.5 Technical Requirements for NFC

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|--------|--|---|--------------------------|---|
| 4.5.1 | Basic RF requirements | NFC Forum Certification for applicable ISO/IEC Standards ETSI EN 300.330 is applicable | Compliance | |
| 4.5.2 | Frequency of operation 13.56 MHz band <i>Note: Frequency of operation requirements are as per the latest NFAP and GSRs issued by WPC and the requirements in NFAP and GSRs supersede the requirements listed here.</i> | Applicant to declare and submit test results pertaining to all the frequency bands of operation for the equipment stating that they are as per the provisions of latest NFAP. | Compliance | |
| 4.5.3 | EIRP | As per the provisions of latest NFAP and GSRs issued by WPC | Compliance | Note: No information is available for power levels in 13.56 MHz band |

4.6 Technical Requirements for Bluetooth Low Energy (BLE)

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|--------|--|---|--------------------------|---------|
| 4.6.1. | Basic RF requirements | Conformance to IEEE 15.1, Bluetooth Special Interest Group (SIG) Product compliance accordance with TEC specification- SD/RAD-01/01.SEP 2005 ETSI EN 300.328.V2.1.1 | Compliance | |
| 4.6.2. | Frequency of operation A. 2.4 GHz band as per latest NFAP provisions. <i>Note: Frequency of operation requirements are as per the latest NFAP and GSRs issued by WPC and the requirements in NFAP and GSRs supersede the requirements listed here.</i> | Current National Frequency Allocation Plan | Compliance | |
| 4.6.3. | EIRP A. Maximum Transmitted Power: 1W (in a spread of 10 MHz or higher) B. Maximum effective radiated power: 4W. | As per the provisions of latest NFAP and GSRs issued by WPC | Compliance | |

| | | | | |
|--|--|--|--|--|
| | <p>C. Maximum antenna height: 5 metres above the roof-top of an existing authorised building</p> <p><i>Note: EIRP requirements are as per the latest NFAP and GSRs issued by WPC and the requirements in NFAP and GSRs supersede the requirements listed here.</i></p> | | | |
|--|--|--|--|--|

4.7 Technical Requirements for USB

As per the technical requirement of ER of USB

4.8 Technical Requirements for Wi-Fi

As per the technical requirement of ER of Wi-Fi

4.9 Technical Requirements for Broadband

As per the technical requirement of ER of Broadband

5 Other Requirements

| Clause | Parameter | Standard | Limits/ Results expected | Remarks |
|-------------|---|--|--------------------------|---------|
| 5.1. | Identification of Equipment for GSM/UMTS/LTE | | | |
| a) | Each device shall have a unique 'International Mobile Station Equipment Identity' (IMEI) which shall not be with all zeros/ null/ invalid IMEI. | GSMA Official Document TS.06, 2017 - IMEI Allocation and Approval Process Test Procedure: Manufacturer shall mention the suitable procedure for testing IMEI by connecting device to smart phone/ tablet/ PC and without using any specialised test equipment | Compliance | |
| 5.2. | Identification of Equipment for CDMA 2000 | | | |
| a) | Each device shall be allocated a unique 'Mobile Equipment Identifier (MEID/ESN)' which shall not be with all zeroes/ null/ invalid MEID/ESN. | Similar Procedure as in Clause 5.1. above | Compliance | |

| | | | | |
|--------------------|---|--|-------------------|--|
| <p>5.3.</p> | <p>Identification of Equipment for technologies other than cellular (BLE, NFC, Wi-Fi etc.)</p> <p>Each individual gateway shall have a unique “Media Access Control address” (MAC address) mentioned in the label attached to it, by which it shall be uniquely identified within the network.</p> | <p>Test Procedure:</p> <p>Manufacturer shall mention the suitable procedure for testing MAC address/ any other unique ID by connecting device to smart phone/ tablet/ PC and without using any specialised test equipment</p> | <p>Compliance</p> | |
| <p>5.4.</p> | <p>IPv6 Compliance</p> <p>All data (Packet) enabled devices shall be capable of carrying IPv6 traffic either on dual stack (IPv4v6) or on native IPv6 compliant</p> | <p>For IPv6: RFC 2460: Clause no. 3, 4.1, 4.2, 4.3, 4.4</p> <p>For Dual stack: RFC 4213: Clause 2.1 & Clause 2.2</p> <p>(Note: Date of implementation will be as per DoT policy)</p> | <p>Compliance</p> | |