



**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi-110001

## **CERTIFICATE OF DESIGNATION**

**M/s BIRLA FURUKAWA FIBRE OPTICS PRIVATE LIMITED  
(OPTICAL FIBRE TESTING LABORATORY), GOA**

has been assessed and designated as Conformity Assessment Body (CAB)  
for its facilities at

**PLOT No's.: L-62 TO L-64, VERNA INDUSTRIAL ESTATE, VERNA,  
SOUTH GOA, GOA – 403 722**

**In the field of Testing**

**Certificate No. TEC/MRA/CAB/IND-D/105**

**Issue Date: 21/01/2025**

**Validity: 21/01/2025 to 20/01/2028**

**This Certificate remains valid for the Scope of Designation as specified in the Annexure subject to the continued validity of NABL Accreditation and satisfied compliance to the Standards/specifications against which lab has been designated and strict compliance to the relevant terms and conditions of TEC CAB Designation Scheme.**

(To see the scope of designation of this laboratory, you may also visit TEC website [www.tec.gov.in](http://www.tec.gov.in))

**Signed for and on behalf of TEC**

Digitally signed by  
Sanjeev Kumar Arya  
Date: 21-01-2025 16:31:49  
**Sanjeev Kumar Arya**  
**Director (CA)**  
**For Designating Authority**  
**TEC**

**Certificate No: TEC/MRA/CAB/IND-D/105 dated 21/01/2025 issued to  
M/s Birla Furukawa Fibre Optics Private Limited  
(Optical Fibre Testing Laboratory), Goa  
Plot No's.: L-62 to L-64, Verna Industrial Estate,  
Verna, South Goa, – 403 722**



**Validity: -21/01/2025 to 20/01/2028**

### **Terms & Conditions**

This certificate is issued as per the terms and conditions stipulated in the TEC SCHEME FOR DESIGNATING DOMESTIC CONFORMITY ASSESSMENT BODIES AND CERTIFICATION BODIES FOR CONFORMITY ASSESSMENT AND CERTIFICATION OF TELECOMMUNICATION EQUIPMENT ISSUE 3 NO. TEC 04019:2023.

Some of the conditions are reiterated as under:

#### **A. Obligations of the Designated CAB.**

1. It shall ensure that it maintains its accreditation status from any recognised Indian accreditation body like NABL during validity period of certificate.
2. It shall follow the stipulated procedures, rules and policies laid down by Designating Authority (DA) or Mutual Recognition Agreement (MRA)\* partner for testing and evaluation.
3. In respect of tests for which it is seeking designation, it shall have no interest whatsoever in any business to carry on testing in an unfair or biased manner.
4. It shall fully indemnify DA from and against all liabilities, damages, claims, costs, and expenses incurred or sustained by DA as a result of any action taken or omitted by DA relating to the process of designation.
5. It shall comply with DA's or MRA partner's terms and conditions for designation and recognition as modified from time to time.
6. It shall be under obligation to participate in the online process prescribed by TEC for test and certification against TEC's GR/IR/ER and standards.
7. It shall have a record system which shall have a retention period of at least 5 years for documents related to the equipment testing. It shall maintain all the relevant documents including list of products submitted for testing, product-wise testing and evaluation reports. These documents shall be produced before the DA within seven days, as and when required.
8. It shall ensure the Intellectual Property Rights of the customers in the course of testing by maintaining professional ethics, secrecy and keeping all the product related information confidential.

\*Applicable only if recognized by MRA (Mutual Recognition Agreement) partner.

9. It shall notify the DA in writing of occurrence of any of the following incident(s) within 2 weeks of its occurrence
  - a) Cessation of its business of conformity assessment for which it is Designated or accredited
  - b) Changes in its legal, commercial, or Organisational status
  - c) Changes, which may affect continuing compliance with any of the criteria or requirement specified by DA or MRA partner.
  - d) Change of premises

## **B. REFERENCE TO DESIGNATION STATUS**

1. Designated CABs may advertise their designation status with regard to standards or parts thereof which are included in the scope of designation.
2. The advertisement should not imply, or otherwise suggest that DA or MRA Partner has endorsed the product or imply that the designated CAB is an agent or representative of DA or MRA Partner.
3. CABs whose designations have been suspended or withdrawn for any reason, shall discontinue advertisement of their designated status and not make any misleading statements regarding their designation status.

## **C. POST-DESIGNATION SURVEILLANCE**

As and when required, DA shall conduct surveillance assessments and other non-routine assessments on the Designated CABs to ensure that standards of practices are maintained as well as to investigate complaints made against them.

## **D. SUSPENSION OR WITHDRAWAL OF DESIGNATION**

1. DA shall suspend or withdraw the designation of a CAB if
  - a. Its accreditation is withdrawn.
  - b. It is found that the CAB is not complying with the stipulated criteria or requirements.
  - c. It is guilty of any offence involving fraud or dishonesty.
  - d. DA concludes that there is a just cause for withdrawing the designation.
2. A CAB whose designation, and recognition in case of MRA, has been suspended or withdrawn shall be removed from the list of designated CABs, in case it fails to take corrective measures.
3. DA shall keep the designation of a Designated CAB under suspension, until the completion of formal review process.

## **E. AMENDMENT TO THE SCHEME**

DA reserves the rights to amend the scheme, as and when required, for the purpose of streamlining designation process.

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 1 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
---------	---------------------------	-----------------------------------	------------------------

Sl. No.	Product	Test Parameters with Standard		Standards
1.	Optical Fibre – Single Mode-ITU-T G.652.D	Geometrical Characteristics	Mode Field Diameter at 1310 nm IEC 60793-1-45	TEC ER No. TEC70112401
			Cladding Diameter IEC 60793-1-20	TEC ER No. TEC70012401
			Cladding Non-circularity IEC 60793-1-20	TEC ER No. TEC70012401
			Core Clad concentricity error IEC 60793-1-20	TEC ER No. TEC70012401
			Coating diameter IEC 60793-1-21	TEC ER No. TEC70012401
			Coating /Cladding concentricity IEC 60793-1-21	TEC ER No. TEC70012401
		Transmission Characteristics (Attenuation of uncabled Fibre)	At 1310 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1550 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1490 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1270 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Water Peak attenuation at 1380 to 1390 nm IEC 60793-1-40	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 2 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.652.D</b>	<b>Transmission Characteristics (Attenuation of uncabled Fibre)</b>	Sudden irregularity in attenuation IEC 60793-1-40 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC 60793-1-42 TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-42 TEC ER No. TEC70012401
			In 1285 nm -1330 nm band IEC 60793-1-42 TEC ER No. TEC70012401
			In 1270 nm-1340 nm band IEC 60793-1-42 TEC ER No. TEC70012401
			Zero Dispersion Slope IEC 60793-1-42 TEC ER No. TEC70012401
			Zero Dispersion Wavelength range IEC 60793-1-42 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	Uncabled Fiber IEC 60793-1-48 TEC ER No. TEC70012401
			Link design value for un-cabled fibre IEC 60793-1-48 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Cable Cutoff Wavelength IEC 60793-1-44 TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 3 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
---------	---------------------------	-----------------------------------	------------------------

	<b>Optical Fibre – Single Mode-ITU-T G.652.D</b>	<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fiber is coiled with 100 turns on 60 ± 1.0 mm diameter mandrel IEC 60793-1-47	TEC ER No. TEC70012401
			Change in attenuation when fiber is coiled with 1 turn around 32 ± 0.5 mm diameter mandrel IEC 60793-1-47	TEC ER No. TEC70012401
			Change in attenuation when fiber is coiled with 100 turns on 50 ± 0.5 mm diameter mandrel IEC 60793-1-47	TEC ER No. TEC70012401
		<b>Mechanical Characteristics</b>	Proof Test for Minimum Strain Level IEC 60793-1-30	TEC ER No. TEC70012401
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32	TEC ER No. TEC70012401
			Dynamic Tensile Strength (Unaged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 4 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.652.D</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Temperature Cycle Test: Temperature dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51
			Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.:** L-62 to I-64, Verna Industrial Estate,  
Verna, South Goa, – 403 722

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 5 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.652.D</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour qualification for color Fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401
	<b>Optical Fibre – Single Mode-ITU-T G.655</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1550 nm IEC 60793-1-45	TEC ER No. TEC70012401
			Cladding Diameter IEC 60793-1-20	TEC ER No. TEC70012401
			Cladding non-circularity IEC 60793-1-20	TEC ER No. TEC70012401
			Core Clad Concentricity error IEC 60793-1-20	TEC ER No. TEC70012401
			Coating Diameter IEC 60793-1-21	TEC ER No. TEC70012401
			Coating /Cladding Concentricity IEC 60793-1-21	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Attenuation of uncabled Fibre)</b>	At 1550 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Sudden irregularity in attenuation IEC 60793-1-40	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 6 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.655</b>	<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1530 nm to 1565 nm IEC 60793-1-42
			At 1565 nm to 1625 nm IEC 60793-1-42
			Dispersion Slope at 1550 nm IEC 60793-1-42
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	for Uncabled Fiber IEC 60793-1-48
			Link design value for Un-cabled Fibre IEC 60793-1-48
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Cable Cut-off Wavelength IEC 60793-1-44
		<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fiber is coiled with 100 turns on $60 \pm 1.0$ mm diameter mandrel IEC 60793-1-47
			Change in attenuation when fiber is coiled with 1 turn around $32 \pm 0.5$ mm diameter mandrel IEC 60793-1-47
		<b>Mechanical Characteristics</b>	Proof test for Minimum Strain Level IEC 60793-1-30
			Peak Stripability Force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 7 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.655</b>	<b>Mechanical Characteristics</b>	Dynamic Tensile Strength (Un aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401
		<b>Environmental Characteristics of Fiber for both color and Uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC ER No. TEC70012401
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC ER No. TEC70012401
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53	TEC ER No. TEC70012401
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited  
(Optical Fibre Testing Laboratory), Goa  
Plot No's.: L-62 to I-64, Verna Industrial Estate,  
Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 8 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.655</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor fibres</b>	Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51	TEC ER No. TEC70012401
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour qualification for color fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401
	<b>Optical Fibre – Single Mode-ITU-T G.656</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1550 nm IEC 60793-1-45	TEC ER No. TEC70012401
			Cladding Diameter IEC 60793-1-20	TEC ER No. TEC70012401
			Cladding Non-Circularity IEC 60793-1-20	TEC ER No. TEC70012401
			Core Clad Concentricity Error IEC 60793-1-20	TEC ER No. TEC70012401
			Coating Diameter IEC 60793-1-21	TEC ER No. TEC70012401
			Coating /Cladding Concentricity IEC 60793-1-21	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 9 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.656</b>	<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	At 1460 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1550 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1383 nm IEC 60793-1-40 TEC ER No. TEC70012401
			Sudden irregularity in attenuation IEC 60793-1-40 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1460 nm to 1550 nm IEC 60793-1-42 TEC ER No. TEC70012401
			At 1550 nm to 1625 nm IEC 60793-1-42 TEC ER No. TEC70012401
			Dispersion Slope at 1550 nm IEC 60793-1-42 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	For Uncabled Fiber IEC 60793-1-48 TEC ER No. TEC70012401
			Link Design Value for Un-cabled Fibre IEC 60793-1-48 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Cable Cut-off wavelength IEC 60793-1-44 TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 10 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.656</b>	<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	Change in attenuation when fiber is coiled with 100 turns on $60 \pm 1.0$ mm diameter mandrel IEC 60793-1-47
			Change in attenuation when fiber is coiled with 1 turn around $32 \pm 0.5$ mm diameter mandrel IEC 60793-1-47
		<b>Mechanical Characteristics</b>	Proof Test for Minimum Strain Level IEC 60793-1-30
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32
			Dynamic Tensile Strength (Un aged) IEC 60793-1-31
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33
			Fiber Curl IEC 60793-1-34

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 11 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.656</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51
			Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 12 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.656</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour Qualification for color fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401
	<b>Optical Fibre – Single Mode-ITU-T G.657.A1</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm IEC 60793-1-45	TEC ER No. TEC70012401
			Cladding Diameter IEC 60793-1-20	TEC ER No. TEC70012401
			Cladding Non-Circularity IEC 60793-1-20	TEC ER No. TEC70012401
			Core Clad Concentricity Error IEC 60793-1-20	TEC ER No. TEC70012401
			Coating Diameter (i) 250 µm Fibre (ii) 200µm Fibre IEC 60793-1-21	TEC ER No. TEC70012401
			Coating /Cladding Concentricity (i) 250 µm Fibre (ii) 200 µm Fibre IEC 60793-1-21	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 13 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A1</b>	<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	At 1310 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1550 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1490 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1270 nm IEC 60793-1-40 TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40 TEC ER No. TEC70012401
			Water Peak attenuation at 1380 nm to 1390 nm IEC 60793-1-40 TEC ER No. TEC70012401
			Sudden irregularity in attenuation IEC 60793-1-40 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC60793-1-42 TEC ER No. TEC70012401
			At 1625 nm IEC60793-1-42 TEC ER No. TEC70012401
			In 1285 nm-1330 nm Band IEC60793-1-42 TEC ER No. TEC70012401
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	In 1270 nm-1340 nm Band IEC60793-1-42 TEC ER No. TEC70012401
			Zero Dispersion Slope IEC60793-1-42 TEC ER No. TEC70012401
			Zero Dispersion Wavelength Range IEC60793-1-42 TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 14 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A1</b>	<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	For Uncabled Fiber IEC 60793-1-48
			Link design value for un-cabled Fibre IEC 60793-1-48
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Fiber cut off wavelength for Fibre used in Patch cords & Pig-tails IEC 60793-1-44
			Cable cut-off wavelength IEC 60793-1-44
		<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	Change in attenuation when Fibre is coiled with 10 turns on 15 mm radius mandrel IEC 60793-1-47
			Change in attenuation when Fibre is coiled with 1 turn on 10 mm radius mandrel IEC 60793-1-47
		<b>Mechanical Characteristics</b>	Proof test for Minimum Strain Level IEC 60793-1-30
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp heat aged) (i) 250 µm fibre (ii) 200µm fibre IEC 60793-1-32
			Dynamic Tensile Strength(Un aged) IEC 60793-1-31

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 15 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A1</b>	<b>Mechanical Characteristics</b>	Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401
		<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC ER No. TEC70012401
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC ER No. TEC70012401
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53	TEC ER No. TEC70012401
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 16 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A1</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50
		<b>Colour qualification for color Fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219
	<b>Optical Fibre – Single Mode-ITU-T G.657.A2</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm IEC 60793-1-45
			Cladding Diameter IEC 60793-1-20
			Cladding Non-Circularity IEC 60793-1-20
			Core Clad Concentricity Error IEC 60793-1-20
			Coating Diameter (i) 250 µm fibre (ii) 200 µm fibre IEC 60793-1-21

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 17 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/ Product	Test Parameter or Type of Testing		Standard/ Specification
	Optical Fibre – Single Mode- ITU-T G.657.A2	Geometrical Characteristics	Coating /Cladding Concentricity (i) 250µm fibre (ii) 200µm fibre IEC 60793-1-21	TEC ER No. TEC70012401
		Transmission Characteristics (Attenuation of Uncabled Fibre)	At 1310 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1550 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1490 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1270 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Water Peak attenuation at 1380 nm to 1390 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Sudden irregularity in attenuation IEC 60793-1-40	TEC ER No. TEC70012401
			Transmission Characteristics (Chromatic Dispersion)	At 1550 nm IEC60793-1-42
		At 1625 nm IEC60793-1-42		TEC ER No. TEC70012401
		In 1285 nm-1330 nm Band IEC60793-1-42		TEC ER No. TEC70012401
		In 1270 nm-1340 nm Band IEC 60793-2-50 and IEC60793-1-42		TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 18 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A2</b>	<b>Transmission Characteristics (Chromatic Dispersion)</b>	Zero Dispersion Slope IEC60793-1-42
			Zero Dispersion Wavelength Range IEC60793-1-42
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	For Uncabled Fiber IEC 60793-1-48
			Link Design Value for Un-Cabled Fibre IEC 60793-1-48
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Fiber cut off wavelength for Fibre used in Patch cords & Pig-tails IEC 60793-1-44
			Cable cut-off wavelength IEC 60793-1-44
		<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when Fibre is coiled with 10 turns on 15 mm radius mandrel IEC 60793-1-47
			Change in attenuation when Fibre is coiled with 1 turn on 10 mm radius mandrel IEC 60793-1-47
			Change in attenuation when Fibre is coiled with 1 turn on 7.5 mm radius mandrel IEC 60793-1-47

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited  
(Optical Fibre Testing Laboratory), Goa  
Plot No's.: L-62 to I-64, Verna Industrial Estate,  
Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 19 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A2</b>	<b>Mechanical Characteristics</b>	Proof Test for Minimum Strain Level IEC 60793-1-30	TEC ER No. TEC70012401
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) (i) 250 µm fibre (ii) 200 µm fibre IEC 60793-1-32	TEC ER No. TEC70012401
			Dynamic Tensile Strength(Un aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401
		<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC ER No. TEC70012401
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 20 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.A2</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at $23 \pm 2^{\circ}\text{C}$ IEC 60793-1-53	TEC ER No. TEC70012401
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at $85 \pm 2^{\circ}\text{C}$ IEC 60793-1-51	TEC ER No. TEC70012401
			Retention of Coating Color: Coated fibre aged for 30 days at $85^{\circ}\text{C}$ temperature with 95% Humidity and then 20 days in $85^{\circ}\text{C}$ dry heat IEC 60793-1-51	TEC ER No. TEC70012401
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at $85^{\circ}\text{C}$ temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour qualification for color fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401
	<b>Optical Fibre – Single Mode-ITU-T G.657.B3</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm IEC 60793-1-45	TEC ER No. TEC70012401
			Cladding Diameter IEC 60793-1-20	TEC ER No. TEC70012401
			Cladding Non-Circularity IEC 60793-1-20	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 21 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
---------	---------------------------	-----------------------------------	------------------------

	<b>Optical Fibre – Single Mode-ITU-T G.657.B3</b>	<b>Geometrical Characteristics</b>	Core Clad Concentricity Error IEC 60793-1-20	TEC ER No. TEC70012401
			Coating Diameter IEC 60793-1-21	TEC ER No. TEC70012401
			Coating /Cladding Concentricity IEC 60793-1-21	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	At 1310 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1550 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1490 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1270 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Water Peak attenuation at 1380 nm to 1390 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Sudden irregularity in attenuation IEC 60793-1-40	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC60793-1-42	TEC ER No. TEC70012401
			Chromatic Dispersion at 1625 nm IEC60793-1-42	TEC ER No. TEC70012401
			In 1285 nm -1330 nm Band IEC60793-1-42	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 22 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.B3</b>	<b>Transmission Characteristics (Chromatic Dispersion)</b>	In 1270 nm-1340 nm Band	TEC ER No. TEC70012401
			IEC 60793-1-42	
			Zero Dispersion Slope	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	IEC 60793-1-42	
			Zero Dispersion Wavelength Range	TEC ER No. TEC70012401
			IEC 60793-1-42	
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	For Uncabled Fiber	TEC ER No. TEC70012401
			IEC 60793-1-48	
		<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Link Design Value for Un-Cabled Fibre	TEC ER No. TEC70012401
			IEC 60793-1-48	
			Fiber Cut off Wavelength for Fibre used in Patch cords & Pig-tails	TEC ER No. TEC70012401
			IEC 60793-1-44	
			Cable Cut-off Wavelength	TEC ER No. TEC70012401
			IEC 60793-1-44	
			Change in attenuation when Fibre is coiled with 1 turns on 10 mm radius mandrel	TEC ER No. TEC70012401
			IEC 60793-1-47	
			Change in attenuation when Fibre is coiled with 1 turn on 5 mm radius mandrel	TEC ER No. TEC70012401
			IEC 60793-1-47	
			Change in attenuation when Fibre is coiled with 1 turn on 7.5 mm radius mandrel	TEC ER No. TEC70012401
			IEC 60793-1-47	

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 23 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.B3</b>	<b>Mechanical Characteristics</b>	Proof test for Minimum Strain Level IEC 60793-1-30	TEC ER No. TEC70012401
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32	TEC ER No. TEC70012401
			Dynamic Tensile Strength(Un aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401
		<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC ER No. TEC70012401
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 24 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.657.B3</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at $23 \pm 2^{\circ}\text{C}$ IEC 60793-1-53	TEC ER No. TEC70012401
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at $85 \pm 2^{\circ}\text{C}$ IEC 60793-1-51	TEC ER No. TEC70012401
			Retention of Coating Color: Coated Fibre aged for 30 days at $85^{\circ}\text{C}$ temperature with 95% Humidity and then 20 days in $85^{\circ}\text{C}$ dry heat IEC 60793-1-51	TEC ER No. TEC70012401
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at $85^{\circ}\text{C}$ temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour qualification for color fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401
	<b>Optical Fibre – Single Mode-ITU-T G.654.D</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm IEC 60793-1-45	TEC ER No. TEC70012401
			Cladding Diameter IEC 60793-1-20	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 25 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.654.D</b>	<b>Geometrical Characteristics</b>	Cladding Non-Circularity IEC 60793-1-20	TEC ER No. TEC70012401
			Core Clad Concentricity Error IEC 60793-1-20	TEC ER No. TEC70012401
			Coating Diameter IEC 60793-1-21	TEC ER No. TEC70012401
			Coating /Cladding Concentricity IEC 60793-1-21	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	at 1550 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1530 nm to 1612 nm IEC 60793-1-40	TEC ER No. TEC70012401
			At 1625 nm IEC 60793-1-40	TEC ER No. TEC70012401
			Sudden irregularity in attenuation IEC 60793-1-40	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC60793-1-42	TEC ER No. TEC70012401
			Dispersion Slope at 1550 nm IEC60793-1-42	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	For Uncabled Fiber IEC 60793-1-48	TEC ER No. TEC70012401
			Link Design Value for Un-Cabled Fibre IEC 60793-1-48	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Cut-off Wavelength)</b>	Cable Cut-off Wavelength IEC 60793-1-44	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 26 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.654.D</b>	<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	Change in attenuation when fiber is coiled with 100 turns on $60 \pm 1.0$ mm diameter mandrel IEC 60793-1-47	TEC ER No. TEC70012401
		<b>Mechanical Characteristics</b>	Proof Test for Minimum Strain Level IEC 60793-1-30	TEC ER No. TEC70012401
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32	TEC ER No. TEC70012401
			Dynamic Tensile Strength (Un aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401
		<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at $-60^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ IEC 60793-1-52	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 27 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre – Single Mode-ITU-T G.654.D</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC ER No. TEC70012401
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53	TEC ER No. TEC70012401
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51	TEC ER No. TEC70012401
			Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51	TEC ER No. TEC70012401
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour qualification for color fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 28 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre-Single Mode-ITU-T G.654.E</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm	TEC ER No. TEC70012401
			IEC 60793-1-45	
			Cladding Diameter	TEC ER No. TEC70012401
			IEC 60793-1-20	
			Cladding Non-Circularity	TEC ER No. TEC70012401
			IEC 60793-1-20	
		<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	Core Clad Concentricity Error	TEC ER No. TEC70012401
			IEC 60793-1-20	
			Coating Diameter	TEC ER No. TEC70012401
			IEC 60793-1-21	
			Coating /Cladding Concentricity	TEC ER No. TEC70012401
			IEC 60793-1-21	
			At 1550 nm	TEC ER No. TEC70012401
			IEC 60793-1-40	
			At 1530 nm -1612 nm	TEC ER No. TEC70012401
			IEC 60793-1-40	
			At 1612 nm to 1625 nm	TEC ER No. TEC70012401
			IEC 60793-1-40	
			Sudden irregularity in attenuation	TEC ER No. TEC70012401
			IEC 60793-1-40	
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm	TEC ER No. TEC70012401
			IEC 60793-1-42	
			Dispersion Slope	TEC ER No. TEC70012401
			IEC 60793-1-42	

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 29 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre-Single Mode-ITU-T G.654.E</b>	<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	For Uncabled Fiber IEC 60793-1-48	TEC ER No. TEC70012401
			Link Design Value for Un-Cabled Fibre IEC 60793-1-48	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Cable Cut-off Wavelength IEC 60793-1-44	TEC ER No. TEC70012401
		<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	Change in attenuation when fiber is coiled with 100 turns on 60 ± 1.0 mm diameter mandrel IEC 60793-1-47	TEC ER No. TEC70012401
		<b>Mechanical Characteristics</b>	Proof test for Minimum Strain Level IEC 60793-1-30	TEC ER No. TEC70012401
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32	TEC ER No. TEC70012401
			Dynamic Tensile Strength(Un aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC ER No. TEC70012401
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC ER No. TEC70012401
			Fiber Curl IEC 60793-1-34	TEC ER No. TEC70012401

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 30 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Optical Fibre-Single Mode-ITU-T G.654.E</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51
			Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 31 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Optical Fibre-Single Mode-ITU-T G.654.E</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC ER No. TEC70012401
		<b>Colour qualification for color fibres</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC ER No. TEC70012401
<b>2.</b>	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.652.D)</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm IEC 60793-1-45	TEC GR No. TEC89010:2021
			Cladding Diameter IEC 60793-1-20	TEC GR No. TEC89010:2021
			Cladding Non- Circularity IEC 60793-1-20	TEC GR No. TEC89010:2021
			Core Clad Concentricity Error IEC 60793-1-20	TEC GR No. TEC89010:2021
			Coating Diameter IEC 60793-1-21	TEC GR No. TEC89010:2021
			Coating /Cladding Concentricity IEC 60793-1-21	TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	At 1310 nm IEC 60793-1-40	TEC GR No. TEC89010:2021
			At 1550 nm IEC 60793-1-40	TEC GR No. TEC89010:2021
			At 1490 nm IEC 60793-1-40	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
(Optical Fibre Testing Laboratory), Goa  
**Plot No's.:** L-62 to I-64, Verna Industrial Estate,  
Verna, South Goa, – 403 722

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 32 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.652.D)</b>	<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	At 1270 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			At 1625 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			Water Peak Attenuation at 1380 nm to 1390 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			Sudden irregularity in attenuation IEC 60793-1-40 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC60793-1-42 TEC GR No. TEC89010:2021
			At 1625 nm IEC60793-1-42 TEC GR No. TEC89010:2021
			In 1285 nm-1330 nm Band IEC60793-1-42 TEC GR No. TEC89010:2021
			In 1270 nm-1340 nm Band IEC60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion Slope IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion Wavelength range IEC 60793-1-42 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	Uncabled Fiber IEC 60793-1-48 TEC GR No. TEC89010:2021
			Link design value for un-cabled fibre IEC 60793-1-48 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 33 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.652.D)</b>	<b>Transmission Characteristics (Cutoff wavelength)</b>	Cable Cut-off wavelength IEC 60793-1-44 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fiber is coiled with 100 turns on 60 ± 1.0 mm diameter mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021
			Change in attenuation when fiber is coiled with 1 turn around 32 ± 0.5 mm diameter mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021
			Change in attenuation when fiber is coiled with 100 turns on 50 ± 0.5 mm diameter mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021
		<b>Mechanical Characteristics</b>	Proof Test for Minimum Strain Level IEC 60793-1-30 TEC GR No. TEC89010:2021
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32 TEC GR No. TEC89010:2021
			Dynamic Tensile Strength (Unaged) IEC 60793-1-31 TEC GR No. TEC89010:2021
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 34 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.652.D)</b>	<b>Mechanical Characteristics</b>	Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC GR No. TEC89010:2021
			Fiber Curl IEC 60793-1-34	TEC GR No. TEC89010:2021
		<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Temperature Cycle Test: Temperature dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC GR No. TEC89010:2021
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC GR No. TEC89010:2021
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53	TEC GR No. TEC89010:2021
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 35 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.652.D)</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor Fibres</b>	Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51	TEC GR No. TEC89010:2021
		<b>Colour qualification</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC GR No. TEC89010:2021
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.655)</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1550 nm IEC 60793-1-45	TEC GR No. TEC89010:2021
			Cladding Diameter IEC 60793-1-20	TEC GR No. TEC89010:2021
			Cladding non-circularity IEC 60793-1-20	TEC GR No. TEC89010:2021
			Core Clad Concentricity error IEC 60793-1-20	TEC GR No. TEC89010:2021
			Coating Diameter IEC 60793-1-21	TEC GR No. TEC89010:2021
			Coating /Cladding Concentricity IEC 60793-1-21	TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Attenuation of uncabled Fibre)</b>	At 1550 nm IEC 60793-1-40	TEC GR No. TEC89010:2021
			At 1625 nm IEC 60793-1-40	TEC GR No. TEC89010:2021
			Sudden irregularity in attenuation IEC 60793-1-40	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 36 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
---------	---------------------------	-----------------------------------	------------------------

Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.655)	Transmission Characteristics (Chromatic Dispersion)	At 1530 nm to 1565 nm IEC 60793-1-42	TEC GR No. TEC89010:2021
		At 1565 nm to 1625 nm IEC 60793-1-42	TEC GR No. TEC89010:2021
		Dispersion Slope at 1550 nm IEC 60793-1-42	TEC GR No. TEC89010:2021
	Transmission Characteristics (Polarization Mode Dispersion)	for Uncabled Fiber IEC 60793-1-48	TEC GR No. TEC89010:2021
		Link design value for Un-cabled Fibre IEC 60793-1-48	TEC GR No. TEC89010:2021
	Transmission Characteristics (Cutoff Wavelength)	Cable Cut-off Wavelength IEC 60793-1-44	TEC GR No. TEC89010:2021
	Transmission Characteristics (Fibre Macro bend loss)	Change in attenuation when fiber is coiled with 100 turns on 60 ± 1.0 mm diameter mandrel IEC 60793-1-47	TEC GR No. TEC89010:2021
		Change in attenuation when fiber is coiled with 1 turn around 32 ± 0.5 mm diameter mandrel IEC 60793-1-47	TEC GR No. TEC89010:2021
	Mechanical Characteristics	Proof test for Minimum Strain Level IEC 60793-1-30	TEC GR No. TEC89010:2021
		Peak Stripability Force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 37 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.655)</b>	<b>Mechanical Characteristics</b>	Dynamic Tensile Strength (Un aged) IEC 60793-1-31	TEC GR No. TEC89010:2021
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31	TEC GR No. TEC89010:2021
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33	TEC GR No. TEC89010:2021
			Fiber Curl IEC 60793-1-34	TEC GR No. TEC89010:2021
		<b>Environmental Characteristics of Fiber for both color and Uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC GR No. TEC89010:2021
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73	TEC GR No. TEC89010:2021
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53	TEC GR No. TEC89010:2021
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 38 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.655)</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor fibres</b>	Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50
		<b>Colour qualification</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.656)</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1550 nm IEC 60793-1-45
			Cladding Diameter IEC 60793-1-20
			Cladding Non-Circularity IEC 60793-1-20
			Core Clad Concentricity Error IEC 60793-1-20
			Coating Diameter IEC 60793-1-21
			Coating /Cladding Concentricity IEC 60793-1-21

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** M/s Birla Furukawa Fibre Optics Private Limited  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.:** L-62 to I-64, Verna Industrial Estate,  
Verna, South Goa, – 403 722

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 39 of 55**

**Validity:** 21/01/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.656)</b>	<b>Transmission Characteristics (Attenuation of Uncabled Fibre)</b>	At 1460 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			At 1550 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			At 1625 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1383 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			Sudden irregularity in attenuation	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	At 1460 nm to 1550 nm	TEC GR No.
			IEC 60793-1-42	TEC89010:2021
			At 1550 nm to 1625 nm	TEC GR No.
			IEC 60793-1-42	TEC89010:2021
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Dispersion Slope at 1550 nm	TEC GR No.
			IEC 60793-1-42	TEC89010:2021
		<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	For Uncabled Fiber	TEC GR No.
			IEC 60793-1-48	TEC89010:2021
			Link Design Value for Un-cabled Fibre	TEC GR No.
			IEC 60793-1-48	TEC89010:2021
		<b>Transmission Characteristics (Cutoff Wavelength)</b>	Cable Cut-off wavelength	TEC GR No.
			IEC 60793-1-44	TEC89010:2021
		<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	Change in attenuation when fiber is coiled with 100 turns on 60 ± 1.0 mm diameter mandrel	TEC GR No.
			IEC 60793-1-47	TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 40 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.656)</b>	<b>Transmission Characteristics (Fibre Macro Bend Loss)</b>	Change in attenuation when fiber is coiled with 1 turn around $32 \pm 0.5$ mm diameter mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021
		<b>Mechanical Characteristics</b>	Proof Test for Minimum Strain Level IEC 60793-1-30 TEC GR No. TEC89010:2021
			Peak Stripability force to remove Primary coating of the fiber (Unaged, Water aged, Damp Heat aged) IEC 60793-1-32 TEC GR No. TEC89010:2021
			Dynamic Tensile Strength (Un aged) IEC 60793-1-31 TEC GR No. TEC89010:2021
			Dynamic Tensile Strength- Aged (Damp Heat aged) IEC 60793-1-31 TEC GR No. TEC89010:2021
			Dynamic Fatigue (Unaged and Damp Heat aged) IEC 60793-1-33 TEC GR No. TEC89010:2021
			Fiber Curl IEC 60793-1-34 TEC GR No. TEC89010:2021
		<b>Environmental Characteristics of Fiber for both color and Uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at $-60^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ IEC 60793-1-52 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 41 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.656)</b>	<b>Environmental Characteristics of Fiber for both color and Uncolor fibres</b>	Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C to +85°C and 95% relative humidity EIA/TIA 455-73
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2° C IEC 60793-1-51
			Retention of Coating Color: Coated Fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50
		<b>Colour qualification</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219
			TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 42 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A1)</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm	TEC GR No. TEC89010:2021
			IEC 60793-1-45	
			Cladding Diameter	TEC GR No. TEC89010:2021
			IEC 60793-1-20	
			Cladding Non-circularity	TEC GR No. TEC89010:2021
			IEC 60793-1-20	
			Core Clad concentricity error	TEC GR No. TEC89010:2021
			IEC 60793-1-20	
		<b>Transmission Characteristics (Attenuation of Uncabled fibres)</b>	Coating diameter	TEC GR No. TEC89010:2021
			a) 250µm fibre	
			b) 200µm fibre	
			IEC 60793-1-21	
			Coating /Cladding concentricity	TEC GR No. TEC89010:2021
			a) 250µm fibre	
			b) 200µm fibre	
			IEC 60793-1-21	
			At 1310 nm	TEC GR No. TEC89010:2021
			IEC 60793-1-40	
			At 1550 nm	TEC GR No. TEC89010:2021
			IEC 60793-1-40	
			At 1490 nm	TEC GR No. TEC89010:2021
			IEC 60793-1-40	
			At 1270 nm	TEC GR No. TEC89010:2021
			IEC 60793-1-40	
			At 1625 nm	TEC GR No. TEC89010:2021
			IEC 60793-1-40	

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 43 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A1)</b>	<b>Transmission Characteristics (Attenuation of Uncabled fibres)</b>	Water Peak attenuation at 1380 nm to 1390 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			Sudden irregularity in attenuation IEC60793-1-40 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC 60793-1-42 TEC GR No. TEC89010:2021
			At 1625 nm IEC 60793-1-42 TEC GR No. TEC89010:2021
			In 1285 nm-1330 nm band IEC 60793-1-42 TEC GR No. TEC89010:2021
			In 1270 nm-1340 nm band IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion slope IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion wavelength range IEC 60793-1-42 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	Un-cabled Fiber IEC 60793-1-48 TEC GR No. TEC89010:2021
			Link design value for un-cabled fibre IEC 60793-1-48 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Cut-off wavelength)</b>	Fiber Cut off wavelength for fibre used in Patch cords & Pig-tails(2m sample) IEC 60793-1-44 TEC GR No. TEC89010:2021
			Cable Cut off wavelength IEC 60793-1-44 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 44 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A1)</b>	<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fibre is coiled with 10 turns on 15 mm radius mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021
			Change in attenuation when fibre is coiled with 1 turn on 10 mm radius mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021
		<b>Mechanical Characteristics</b>	Proof Test for minimum strain level IEC 60793-1-30 TEC GR No. TEC89010:2021
			Peak Stripability force to remove primary coating of the fiber (Unaged, Water aged, Damp heat aged) a) 250µm fibre b) 200µm fibre IEC 60793-1-32 TEC GR No. TEC89010:2021
			Dynamic Tensile Strength (Un aged) IEC 60793-1-31 TEC GR No. TEC89010:2021
			Dynamic Tensile Strength Aged (Damp Heat aged) IEC 60793-1-31 TEC GR No. TEC89010:2021
			Dynamic Fatigue (Unaged and Damp heat aged) IEC 60793-1-33 TEC GR No. TEC89010:2021
			Fiber Curl IEC 60793-1-34 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 45 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/ Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A1)</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C TO +85°C and 95% relative humidity EIA/TIA 455-73
			Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2 °C IEC 60793-1-53
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85 ± 2 °C IEC 60793-1-51
			Retention of Coating Color: Coated fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 46 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
---------	---------------------------	-----------------------------------	------------------------

	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A1)</b>		High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC GR No. TEC89010:2021
		<b>Colour qualification</b>	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC GR No. TEC89010:2021
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A2)</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm IEC 60793-1-45	TEC GR No. TEC89010:2021
			Cladding Diameter IEC 60793-1-20	TEC GR No. TEC89010:2021
			Cladding Non-circularity IEC 60793-1-20	TEC GR No. TEC89010:2021
			Core Clad concentricity error IEC 60793-1-20	TEC GR No. TEC89010:2021
			Coating diameter a) 250µm fibre b) 200µm fibre IEC 60793-1-21	TEC GR No. TEC89010:2021
			Coating /Cladding concentricity a) 250µm fibre b) 200µm fibre IEC 60793-1-21	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 47 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A2)</b>	<b>Transmission Characteristics (Attenuation of uncabled fibre)</b>	At 1310 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			At 1550 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			At 1490 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			At 1270 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			At 1625 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			Water peak attenuation at 1380 nm to 1390 nm IEC 60793-1-40 TEC GR No. TEC89010:2021
			Sudden irregularity in attenuation IEC60793-1-40 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC 60793-1-42 TEC GR No. TEC89010:2021
			At 1625 nm IEC 60793-1-42 TEC GR No. TEC89010:2021
			In 1285 nm-1330 nm band IEC 60793-1-42 TEC GR No. TEC89010:2021
			In 1270 nm – 1340 nm band IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion Slope IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion Wavelength range IEC 60793-1-42 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 48 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A2)</b>	<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	Uncabled Fiber IEC 60793-1-48
			Link design value for un-cabled fibre IEC 60793-1-48
		<b>Transmission Characteristics (Cut off wavelength)</b>	Fiber Cut off wavelength for fibre used in Patch cords & Pig-tails (2m sample) IEC 60793-1-44
			Cable Cut-off wavelength IEC 60793-1-44
		<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fibre is coiled with 10 turns on 15 mm radius mandrel IEC 60793-1-47
			Change in attenuation when fibre is coiled with 1 turn on 10 mm radius mandrel IEC 60793-1-47
			Change in attenuation when fibre is coiled with 1 turn on 7.5 mm radius mandrel IEC 60793-1-47
		<b>Mechanical Characteristics</b>	Proof test for minimum strain level IEC 60793-1-30

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



## **SCOPE OF DESIGNATION** **(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 49 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A2)</b>	<b>Mechanical Characteristics</b>	Peak Stripability force to remove primary coating of the fiber (Unaged, Water aged, Damp heat aged) a) 250µm fibre b) 200µm fibre IEC 60793-1-32	TEC GR No. TEC89010:2021
			Dynamic Tensile Strength (Un aged) IEC 60793-1-31	TEC GR No. TEC89010:2021
			Dynamic Tensile Strength Aged (Damp heat aged) IEC 60793-1-31	TEC GR No. TEC89010:2021
			Dynamic Fatigue Unaged and Damp heat aged IEC 60793-1-33	TEC GR No. TEC89010:2021
			Fiber Curl IEC 60793-1-34	TEC GR No. TEC89010:2021
		<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52	TEC GR No. TEC89010:2021
			Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C TO +85°C and 95% relative humidity EIA/TIA 455-73	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 50 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.A2)</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23±2°C IEC 60793-1-53	TEC GR No. TEC89010:2021
			Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85±2°C IEC 60793-1-51	TEC GR No. TEC89010:2021
			Retention of Coating Color: Coated fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51	TEC GR No. TEC89010:2021
			High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC GR No. TEC89010:2021
		<b>Colour qualification</b>	MEK RUB Test(Methyl Ethyl Ketone) IEC 60794-1-219	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 51 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.B3)</b>	<b>Geometrical Characteristics</b>	Mode Field Diameter at 1310 nm	TEC GR No.
			IEC 60793-1-45	TEC89010:2021
			Cladding Diameter	TEC GR No.
			IEC 60793-1-20	TEC89010:2021
			Cladding Non-circularity	TEC GR No.
			IEC 60793-1-20	TEC89010:2021
			Core Clad concentricity error	TEC GR No.
		<b>Transmission Characteristics (Attenuation of uncabled Fibre)</b>	IEC 60793-1-20	TEC89010:2021
			Coating diameter	TEC GR No.
			IEC 60793-1-21	TEC89010:2021
			Coating /Cladding concentricity	TEC GR No.
			IEC 60793-1-21	TEC89010:2021
			At 1310 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			At 1550 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			At 1490 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			At 1270 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			At 1625 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			Water peak attenuation at 1380 nm to 1390 nm	TEC GR No.
			IEC 60793-1-40	TEC89010:2021
			Sudden irregularity in attenuation	TEC GR No.
			IEC 60793-1-40	TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 52 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.B3)</b>	<b>Transmission Characteristics (Chromatic Dispersion)</b>	At 1550 nm IEC 60793-1-42 TEC GR No. TEC89010:2021
			At 1625 nm IEC 60793-1-42 TEC GR No. TEC89010:2021
			In 1285 nm-1330 nm band IEC 60793-1-42 TEC GR No. TEC89010:2021
			In 1270 nm-1340 nm band IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion Slope IEC 60793-1-42 TEC GR No. TEC89010:2021
			Zero Dispersion Wavelength range IEC 60793-1-42 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Polarization Mode Dispersion)</b>	Uncabled Fiber IEC 60793-1-48 TEC GR No. TEC89010:2021
			Link design value for un-cabled fibre IEC 60793-1-48 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Cut-off wavelength)</b>	Fiber Cutoff wavelength for fibre used in patch cords & Pig-tails IEC 60793-1-44 TEC GR No. TEC89010:2021
			Cable Cutoff Wavelength IEC 60793-1-44 TEC GR No. TEC89010:2021
		<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fibre is coiled with 1 turn on 10 mm radius mandrel IEC 60793-1-47 TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 53 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.B3)</b>	<b>Transmission Characteristics (Fibre Macro bend loss)</b>	Change in attenuation when fibre is coiled with 1 turn on 7.5 mm radius mandrel IEC 60793-1-47
			Change in attenuation when fibre is coiled with 1 turn on 5 mm radius mandrel IEC 60793-1-47
		<b>Mechanical Characteristics</b>	Proof test for minimum strain level IEC 60793-1-30
			Peak Stripability force to remove primary coating of the fiber (Unaged, Water aged, Damp heat aged) IEC 60793-1-32
			Dynamic Tensile Strength (Un aged) IEC 60793-1-31
			Dynamic Tensile Strength Aged (Damp heat aged) IEC 60793-1-31
			Dynamic Fatigue (Unaged and Damp heat aged) IEC 60793-1-33
			Fiber Curl IEC 60793-1-34
		<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature Cycle Test: Temperature Dependence of Attenuation: Induced Attenuation at 1550 nm and 1625 nm at -60°C to +85°C IEC 60793-1-52

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to L-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 54 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing	Standard/Specification
	<b>Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.B3)</b>	<b>Environmental Characteristics of Fiber for both color and uncolor fibres</b>	Temperature-Humidity Cycle Test: Induced attenuation at 1550 nm and 1625 nm at -10°C TO +85°C and 95% relative humidity EIA/ TIA 455-73
		Water Immersion Test: Induced attenuation at 1550 nm and 1625 nm due to water immersion at 23 ± 2°C IEC 60793-1-53	TEC GR No. TEC89010:2021
		Accelerated Aging (Dry Heat) Test: Induced attenuation at 1550 nm and 1625 nm due to Temperature aging at 85± 2°C IEC 60793-1-51	TEC GR No. TEC89010:2021
		Retention of Coating Color: Coated fibre aged for 30 days at 85°C temperature with 95% Humidity and then 20 days in 85°C dry heat IEC 60793-1-51	TEC GR No. TEC89010:2021
		High Temperature and High Humidity (Damp Heat) Test: Induced attenuation at 1550 nm & 1625 nm at 85°C temperature and 85% Relative Humidity for 30 days IEC 60793-1-50	TEC GR No. TEC89010:2021

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**



**GOVERNMENT OF INDIA  
MINISTRY OF COMMUNICATIONS  
DEPARTMENT OF TELECOMMUNICATIONS  
TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name: M/s Birla Furukawa Fibre Optics Private Limited**  
**(Optical Fibre Testing Laboratory), Goa**  
**Plot No's.: L-62 to I-64, Verna Industrial Estate,**  
**Verna, South Goa, – 403 722**

**Certificate Number: TEC/MRA/CAB/IND-D/105**

**Page 55 of 55**

**Validity: 21/01/2025 to 20/01/2028**

**Last Amended on: ----**

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
	Raw Material for Manufacturing of Optical Fibre Cable- (Optical Fibre –ITU-T G.657.B3)	Colour qualification	MEK RUB Test (Methyl Ethyl Ketone) IEC 60794-1-219	TEC GR No. TEC89010:2021

Digitally signed by  
Rajeev Ranjan  
Date: 21-01-2025 16:33:51

**AD (CA), TEC**

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**Government of India**  
**Department of Telecommunications**  
**Telecommunication Engineering Centre**  
**Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi-110001**

**No. 1-122/2024-सी.ए./टी.ई.सी.**

**Dated: 13.05.2025**

**To,**  
**Sh. SWAPNIL PATERIA, Director,**  
**M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre Testing Laboratory), Goa,**  
**Plot Nos.: L-62 to L-64, Verna Industrial Estate, Verna, South Goa- 403722**  
**Mob: +91- 7507544772**  
**E-Mail: [spateria@birlafurukawa.com](mailto:spateria@birlafurukawa.com), [bgautam@birlafurukawa.com](mailto:bgautam@birlafurukawa.com)**

**Subject: Enhancement of Scope of CAB Designation of M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre Testing Laboratory), Goa.**

**Ref: TEC CAB Designation Certificate no. TEC/MRA/CAB/IND-D/105 dated 21.01.2025.**

It is informed that the existing scope of Designation of M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre Testing Laboratory), Goa as CONFORMITY ASSESSMENT BODY (CAB) of TEC has been enhanced in respect of following test parameters on account of inclusion of these test parameters in its NABL Scope of Accreditation w.e.f. the date of issue of this letter:

2. In reference to the recommendations of Site visit assessment team, the scope of designation of CAB Certificate no. referred above is hereby enhanced in respect of test parameters of "Cable Material Compatibility test for fibre -Fibre" as per detail mentioned in Annexure attached.
3. All other details, terms and conditions and validity of CAB Designation Certificate no. TEC/MRA/CAB/IND-D/105 dated 21.01.2025 shall remain unchanged.
4. This is issued with the approval of Competent Authority.

Encl: as above

**Digitally signed by**  
**Sanjeev Kumar Arya**  
**Date: 13-05-2025**  
**14:41:08**

(Sanjeev Kumar Arya)  
Director (CA), TEC

Copy to:

1. DDG (WR), DDG (TX), for kind information.

**GOVERNMENT OF INDIA**  
**MINISTRY OF COMMUNICATIONS**  
**DEPARTMENT OF TELECOMMUNICATIONS**  
**TELECOMMUNICATION ENGINEERING CENTRE**  
Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi - 110 001



**SCOPE OF DESIGNATION**  
**(ANNEXURE)**

**Laboratory Name:** TEC/MRA/CAB/IND-D/105 dated 21/01/2025 issued to  
M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre  
Testing Laboratory), Goa, Plot No's.: L-62 To L-64, Verna  
Industrial Estate, Verna, South Goa, Goa – 403 722.

**Certificate Number:** TEC/MRA/CAB/IND-D/105

**Page 1 of 1**

**Validity:** 13/05/2025 to 20/01/2028

**Last Amended on:** ----

Sl. No.	Telecom Equipment/Product	Test Parameter or Type of Testing		Standard/Specification
1.	<b>Optical Fibre-single Mode</b>  (Environmental Characteristics of Fibre for both color and uncolor fibres)	<b>Optical Fibre – ITU-T G.652.D</b>	Cable Material Compatibility test for fibre -Fibre to be aged with filling compound for 30 days at 85 deg C Temperature and 85 percent Relative Humidity Telcordia GR- 20- CORE 2013 Draft IEC 60794-1-219 Annex-Q	TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.655</b>		TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.656</b>		TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.657.A1</b>		TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.657.A2</b>		TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.657.B3</b>		TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.654.D</b>		TEC ER No. TEC70012401
		<b>Optical Fibre- ITU-T G.654.E</b>		TEC ER No. TEC70012401

Digitally signed by  
Rajeev Ranjan  
Date: 13-05-2025  
15:35:36

**\*The validity of Certificate is up to 20/01/2028 or the continued validity of NABL Accreditation, whichever is earlier.**

**Government of India**  
**Department of Telecommunications**  
**Telecommunication Engineering Centre**  
**Gate No. 5, Khurshid Lal Bhawan, Janpath, New Delhi-110001**

No. 1-122/2024-सी.ए./टी.ई.सी.

Dated: 09.05.2025

**Corrigendum**

**Subject: Corrigendum to CAB Designation Certificate No. TEC/MRA/CAB/IND-D/105 dated 21.01.2025 of M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre Testing Laboratory), Goa.**

**Reference: CAB Designation Certificate No. TEC/MRA/CAB/IND-D/105 dated 21.01.2025.**

This is in reference to this office CAB Designation Certificate No. TEC/MRA/CAB/IND-D/105 dated 21.01.2025, issued to M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre Testing Laboratory) Goa.

2. The following modifications have been made to the aforesaid CAB Designation certificate:

- (i) Mode Field Diameter at 1310 nm may be read as Mode Field Diameter at 1550 nm of G.654.D.
- (ii) Mode Field Diameter at 1310 nm may be read as Mode Field Diameter at 1550 nm of G.654.E.
- (iii) Dispersion Slope may be read as Dispersion slope at 1550 nm of G.654.E.

3. All other content of the CAB Designation Certificate No. TEC/MRA/CAB/IND-D/105 dated 21.01.2025 shall remain unchanged.

4. This is issued with the approval of Competent Authority.

Digitally signed by  
Rajeev Ranjan  
Date: 13-05-2025  
15:43:18  
(Rajeev Ranjan)  
AD (CA), TEC

To,  
**Sh. SWAPNIL PATERIA, Director,**  
**M/s Birla Furukawa Fibre Optics Private Limited (Optical Fibre Testing Laboratory), Goa,**  
**Plot Nos.: L-62 to L-64, Verna Industrial Estate, Verna, South Goa- 403722**  
**Mob: +91- 7507544772**  
**E-Mail: [spateria@birlafurukawa.com](mailto:spateria@birlafurukawa.com), [bgautam@birlafurukawa.com](mailto:bgautam@birlafurukawa.com)**

Copy to:

1. DDG (WR), DDG (TX), DDG(TC) for kind information.